

VERVE WORKS WITH YOU

Fair Showers Ltd.
Rode Road
Ringcourt
Ca Caen
Lancashire
T: +44 (0) 156 800 000
E: sales@fairshowers.com

FAIRSHOWERS.COM

VERVE



IN THE BOX

TAKE A MINUTE TO CHECK THE
CONTENTS OF EACH BOX



Part	Quantity
A	1 Pz
B	1 Pz
C	1 Pz
D	2 Pz
E	2 Pz
F	2 Pz
G	2 Pz
H	2 Pz
I	1 Pz
J	1 Pz

INSTALLATION & MAINTENANCE

INSTALLATION TIPS

It is the responsibility of the installer to ensure that the product is installed correctly and due care is given to the instructions.

Your guarantee is void if the instructions have not been followed correctly.

- Please check for all visual defects on the product before installation - such defects will not be accepted after installation of the product.
- For shower enclosures a spirit level should be used to ensure the shower is level - if the shower tray is not level your shower door will wobble.
- Secure vertical wall profiles as level and as an equal distance to from the tray.
- Secure adjustment of wall profile to equal attach side and that all screws are fully tightened.
- Secure hinges are level and securely fitted to the glass.
- Secure magnets are the right orientation and attaching with the correct way.
- Secure silicone used to waterproof your shower enclosure.
- Gels must be taken during assembly, that will not take responsibility where incorrect assembly results in water stress being put on any of the glass components in this product.
- If there are any manufacturing problems please call Fair Service Line on +44 (0) 156 800 000.
- Note: If the problem has been caused by your installation, there will be an initial call-out charge for our technical engineer and subsequent charges to the end user for the problem caused by your installation.

CLEANING

Clean any glass coatings in a standard fashion on all shower doors. This way is clearest coating is applied to the glass surface and ensures that soap deposits and lime scale are easily cleaned off the glass.

Use a soft dedicated mild detergent, rinse off thoroughly.
Use a soft dedicated mild detergent, rinse off thoroughly.
Use a soft dedicated mild detergent, rinse off thoroughly.

Do not use "Bona & Bon" cleaning products on the enclosure as these will cause damage to your shower door. These include acidic based cleaning products, bleaches, solvents or abrasive pads. These will damage the existing seal on the aluminium profiles. To best water stress, regular cleaning of your Fair door will help to prevent the buildup of lime scale. Stubborn deposits of lime scale can be removed with the use of a mild descaler. Remove.
Only use descalers, descalers and lime scale removers with a pH of 10.
The content use of descalers will degrade the finish of the product over time if not thoroughly rinsed off.

MAINTENANCE TIPS

- Check your shower door for functionality periodically.
- Secure that the wheel is free from any grime which may have collected over time.
- Lubricate the wheels and rollers with available first lubricant spray or grease every 6 months.
- Only use non-abrasive cleaning agents on all Fair products and rinse off thoroughly.
- Do not use excessive force when opening and closing your shower door as this will result in shattering.
- Do not hang from your shower door or shower door handle - it is not designed to support excessive weight.

GUARANTEE & AFTERSALES SERVICE

QUALITY GUARANTEED

All Fair products have an unwavering commitment to product quality.

Verve shower doors are covered by a 20-year guarantee against manufacturer defects. This guarantee is valid on the condition that goods are installed and maintained in accordance with the product fitting instructions and test protocols.

Non-glass and detachable parts such as rollers, seals etc. are subject to normal wear and tear during usage and are under guarantee for 12 months from date of purchase.

Please complete your product guarantee card included in the components box or register online at fairshowers.com/register.

All Fair products are CE approved and manufactured in accordance with ISO 9001:2000 Quality Assurance systems. All glass is tough safety glass and produced to EN 12158. Fair products are performance tested to EN 14626, ensuring the highest industry standards to meet.

AFTERSALES & SPARE PARTS SERVICE

Fair is 100% committed to customer service excellence.

We carry a full range of spare parts for each of our product ranges and have dedicated aftercare representatives located within any branch you may have.

If you would like to talk to our customer aftercare team, please contact us on 0156 800 000.

WARNING!

BEFORE YOU INSTALL YOUR SHOWER ENCLOSURE PLEASE READ ALL INSTRUCTIONS. FAILURE TO DO SO MAY LEAD TO INVALIDATION OF YOUR WARRANTY.

The shower tray MUST be fixed 100% level.

Glass door edges are vulnerable. Contact with hard surfaces may result in glass breakage.

The shower enclosure should be tested only on the outside using silicone sealant.

Check walls for electrical cabling or water pipes before drilling.

Your shower enclosure must be inspected 100% before installation. Once the enclosure has been installed no claims of damage or defect will be accepted. Fitting of shower enclosure is acceptance of quality.

The wall plugs supplied with the installation are for use in solid walls. Timber frames, stud partition walls will require alternative fixings.

Shower Tray must be installed 100% level in all directions and sealed at the wall with silicone especially under the profiles of the shower enclosure.

Fair Showers Ltd will not accept responsibility for any loss or damage, however caused, if the shower enclosure has not been installed to the instructions.

