

# Axton Silicone Remover

## S20-L2-REMOV-Sil

Revision: 19/11/2018

Page 1 from 1

**Technical data**

Basis	Based on hydrocarbons
Consistency	Liquid
Density**	Ca. 0,87 g/ml
Viscosity	1400 +/- 600 Poise
Solubility in water	Not soluble
Solubility in other	Soluble in hydrocarbons
Application temperature	5 °C → 30 °C

\* These values may vary depending on environmental factors such as temperature, moisture, and type of substrates. \*\* This information relates to fully cured product.

**Product description**

Axton Silicone Remover is a ready-to-use and fast-working product based on hydrocarbons for removing hardened silicones and MS polymers.

**Properties**

- Fast-working
- Does not drip
- Specifically for silicones and MS polymers

**Applications**

- Removal of old silicone residue, spilled silicone or spilled MS polymers from different kind of surfaces.
- Removes all residue of spilled silicone.

**Packaging**

*Colour:* yellow-transparent

*Packaging:* 100 ml tube

**Shelf life**

5 years in unopened packaging in a dry and cool environment at temperatures between +5°C and +25°C.

**Substrates**

*Substrates:* coated metals, ceramic tiles, laminated plate, painted surfaces, glass, aluminium, some synthetic materials (NOT nylon and PMMA)

*Nature:* dry

**Application method**

*Application method:* Apply on dry ground and dry conditions. Remove cured sealant first with a knife. Apply Silicone Remover on the surface to be cleaned. Leave to work for at least 10 min. Wipe dry with a clean cloth. Repeat if necessary. Wash thoroughly with water to avoid surface degradation.

**Health- and Safety Recommendations**

Use only in well-ventilated areas. In case of contact with eyes, wash immediately with plenty of water. Always wear gloves and goggles. In case of contact with skin, wash with water and soap.

**Remarks**

- Silicone Remover can cause staining on porous surfaces.
- Due to the wide variety of possible plastics and paints and to avoid damage to the surface, a preliminary compatibility test is recommended.

**Liability**

The content of this technical data sheet is the result of tests, monitoring and experience. It is general in nature and does not constitute any liability. It is the responsibility of the user to determine by his own tests whether the product is suitable for the application.

Remark: This technical data sheet replaces all previous versions. The directives contained in this documentation are the result of our experiments and of our experience and have been submitted in good faith. Because of the diversity of the materials and substrates and the great number of possible applications which are out of our control, we cannot accept any responsibility for the results obtained. Since the design, the quality of the substrate and processing conditions are beyond our control, no liability under this publication is accepted. In every case it is recommended to carry out preliminary experiments. Soudal reserves the right to modify products without prior notice.