



## PRODUCT INFORMATION SHEET (ANNEX 5)

Creation date (dd/mm/yyyy) :	31/08/2022
Last update date (dd/mm/yyyy) :	06/09/2022

1	General information	Supplier's name or trade mark	INSPIRE
2		Supplier's address	ADEO Services, 135 rue Sadi Carnot - CS00001, 59790 RONCHIN
3		Model Identifier - Luminaire Supplier reference	HT-FP50W
4		Light sources maker model	HT-FP50W module
5		Date of placement on the market	22/10/2022
6	Type of light source:	Lighting technology used:	LED
7		Light source cap type (or other electric interface)	Direct wired
8		Non-directional (NDLS非定向) or directional	NDLS
9		Mains (MLS市电) or non-mains	MLS
10		Connected light source (CLS):	no
11		Colour-tunable light source:	no
12		Envelope:	no
13		High luminance light source:	no
14		Anti-glare shield:	no
15		Dimmable:	no
16		Energy consumption in on-mode (kWh/1000 h)	50 kWh/1000h
17		Energy efficiency class	E
18		Useful luminous flux ( $\Phi_{use}$ ), indicating if it refers to the flux in a sphere (360°), in a wide cone (120°) or in a narrow cone (90°), expressed in Lm	5500
19		Correlated colour type	single value
20		Correlated colour temperature, rounded to the nearest 100 K, or the range of correlated colour temperatures, rounded to the nearest 100 K that can be set	6500 K
21		On-mode power ( $P_{on}$ ), expressed in W and rounded to the first decimal	50.0 W
22		Standby power ( $P_{stb}$ ), expressed in W and rounded to the second decimal	0.00 W
23		Networked standby power ( $P_{net}$ ) for CLS, expressed in W and rounded to the second decimal	0.00 W
24		Colour rendering index, rounded to the nearest integer, or the range of CRI-values that can be set	80
25		Outer dimensions without separate control gear, lighting control parts and nonlighting control parts, if any (millimetre)	
26		Height (mm)	309.00 mm
27		Width (mm)	148.00 mm
28		Depth (mm)	10.00 mm
29	General product parameters:	Spectral power distribution in the range 250 nm to 800 nm, at full-load (insert picture of the spectral power distribution + name of picture+extension (.jpeg))	HT-FP50W - spectral power distribution.jpg 
30		Claim of equivalent power	yes
31		If yes, equivalent power (W)	366 W
32		Chromaticity coordinates (x and y)	0.3130, 0.3370
33		Peak luminous intensity (cd)	cd
34	Parameters for directional light sources:	Beam angle in degrees (no decimal), or the range of beam angles that can be set	Degrees
35	Parameter for LED and OLED light sources:	R9 colour rendering index value	19
36		Survival factor rounded to the second decimal (>0.xx)	0.90
37		Lumen maintenance factor rounded to the second decimal (>0.xx)	0.95
38		displacement factor ( $\cos \phi_1$ ) rounded to the second decimal	1.00
39		Colour consistency in McAdam ellipses	6.0
40	Parameters for LED and OLED mains lights sources:	Claims that an LED light source replaces a fluorescent light source without integrated ballast of a particular wattage.	-
41		If yes then replacement claim (W) (no decimal)	W
42		Flicker metric ( $P_{st LM}$ ) rounded to the first decimal ERP	0.1
43		Stroboscopic effect metric ( $SVM$ ) rounded to the first decimal ERP	
44		Technical documentation name (in case of light source product)	
45		Light source removing instruction name (in case of containing product)	HT-FP50W - light source removing instruction.pdf