

Product specification	DECOR NAME	
Product type	vinyl panel with composite core - meets the requirements of EN14041:2004+AC:2006	BETON SZARY
Technology	SPC Stone Polymer Composite	
Size	610 x 610 mm	
Thickness	4.0mm	
Wear layer	0.5mm	
Micro bevel	painted bevelled	
Sposób montażu	floating floor, glueless, lock I4F	
Waterproof	yes	
Package	2,233m ²	
Utility class - residential use	EN 685	23 (warranty: 25 years)
Utility class - commercial use	EN 685	33 (warranty: 10 years)
Reaction of fire	EN 13501	Bfl-s1
Abrasion resistance	EN ISO 660-2	group T
Residual indentation	EN ISO 24343-1	≤0.1mm
Castors resistance	EN ISO 4918:2009	type W - 25000 cycles, no damage in the wear layer, no delamination
Dimensional stability	EN ISO 23999:2008	0,10%
Lock strenght	ISO 24334	long side 3,4 kN/m; short side 3,0 kN/m
Slipperiness	EN 13893	DS
Chemical resistance	EN ISO 26987	Index 0 (very good)
UV resistance	EN ISO 105-B02	≥ 6
Thermal conductivity	EN 12524/12667	0,109 W/mk
Thermal resistance	EN 12667	0,045 m ² K/W
Water floor heating	EN 12524/12667	yes - max 28°C
Pentachlorophenol content	EN 14041 Anex B	not found
Formaldehyde emission	EN 717-1	E1
Impact noise reduction	EN ISO 717-2:2013	ΔLw =16 dB
VOC	A+	