

Product specification	NEW SCOTTLAND OAK		
Product type	vinyl panel with composite core - meets the requirements of EN14041:2004+AC:2006		
Technology	SPC Stone Polymer Composite		
Size	122x610x4.0mm		
Thickness	4mm		
Wear layer	0.55mm		
Micro bevel	4 sided		
Sposób montażu	floating floor, glueless, lock 5Gi		
Waterproof	yes		
Package	1.786 m2		
Utility class - residential use	EN 685	23 (warranty: 25 years)	
Utility class - commercial use	EN 685	33 (warranty: 10 years)	
Reaction of fire	EN 13501-1	Rf1-S1	
Abrasion resistance	ASTM D4060-14	Weight loss: 108mg	
Residual indentation	EN433	0.05mm	
Castors resistance	NALFALF 01-2011	No Visible Damage	
Dimensional stability	EN434	< 0.1%	
Slipperiness	DIN51130	R9	
Chemical resistance	EN423	No affected index 0	
Thermal conductivity	EN ISO 10456	0,25 w/(m.K)	
Thermal resistance	EN 12667:2001	0.033(m2.k)/W	
Water floor heating	EN 12524/12667	yes - max 28°C	
Pentachlorophenol content	EN 14041 Anex B	None	
Formaldehyde emission	EN 717-1	None	
STC	ASTM E413-10	53	
IIC	ASTM E989-12	55	
VOC	Reach, A+, DiBt		