

Product identification

Adeo Ref	827520	Adeo Ref	827580
Product EAN	3276007200294	Product EAN	3276007200300
Supplier ref	T046-CFK120-WN3	Supplier ref	T046-CFK120-NN3
Adeo Ref	827519	Adeo Ref	827506
Product EAN	3276007200317	Product EAN	3276007202410
Supplier ref	T046-CFK120-BN3	Supplier ref	T046-CRU120-NN3
Adeo Ref	827513	Adeo Ref	
Product EAN	3276007202403	Product EAN	
Supplier ref	T046-CRU120-WN3	Supplier ref	

Template version history

Version	Status	Date Status	Comments
V.0	Under construction	20/08/2018	Template construction
V.1	Validated construction	30/09/2019	Validated Template

Object

Technical data sheet of products

Technical data

ZHEJIANG TAI-G PHOTOELECTRIC TECHNOLOGY CO.,LTD

No.576,Gaoxin Xiyi Rd,Tongxiang economic development zone,

314500,Tongxiang,Zhejiang,China

Name product	Manoa	Rated frequency	50/60Hz
Power in Watt	6.7W	Ta	40°C
Nett Weight in gram (without batteries, without packaging)	0.14kg	Protection class	II
Size of product: LxIhx in centimetre	Φ12.3x1.8cm	IP number	IP 20(recessed parts of luminaires) /IP44(exposed parts of luminaires)
Accessories included: detailed it	Screw, isolation column, expansion screw tube, card Spring	Module Lumen	1000lm
Weight packaging	0.21kg	Color temperature	4000K/3000K
Size packaging	13*15*2.8cm	Angel beam	118°
Rated voltage	220-240V~	CRI	80
Rated current	55mA	Life time	15000h

Remark: The main technical features could be adjusted by supplier based on different kinds of products.

Photo