

Declaration of Performance

In accordance with the CPR Regulation (EU) N° 305/2011

Axton Façade&Roof&Gutter hybrid polymer Sealant S20-L2-FRG-Hybr

Revision: 19/11/2018 Page 1 from 4

Reference nr DOP: -

Unique identification code of the product type:

Axton Façade&Roof&Gutter hybrid polymer Sealant

Intended use or uses of the construction product:

Sealant for facade for interior and exterior application, intended for use in cold climate. Sealant used for pedestrian walkways for interior application.

Construction product in accordance with applicable harmonised specifications:

EN 15651-1:2012: Type F - EXT-INT-CC: CLASS 25LM

EN 15651-4:2012: Type PW-INT

System or systems of assesment and verification of consistancy of performance of the construction product, as set out in Annex V:

System 3: for essential characteristics

System 3: for reaction to fire

Name and contact address of the manufacturer as required pursuant to Article 11(5):

Soudal NV, Everdongenlaan 18-20, 2300 Turnhout, Belgium

The notified body:

GINGER CEBTP, NB 0074 has carried out Determination of Product Type under system 3.

Soudal NV Everdongenlaan 18 - 20 BE-2300 Turnhout Tel: +32 (0)14-42.42.31 Fax: +32 (0)14-42.65.14 www.soudal.com