


| | | | | | |
|----|--|---|---|-----------|--|
| 1 | General information | Supplier's name or trade mark | INSPIRE | | |
| 2 | | Supplier's address | ADEO Services, 135 rue Sadi Carnot - CS00001, 59790 RONCHIN | | |
| 3 | | Model Identifier - Luminaire Supplier reference | CLEIP2TWC-D3018 WD | | |
| 4 | | Light sources maker model | CLEIP2TWC-D3018 WD | | |
| 5 | | Date of placement on the market | 01/09/2021 | | |
| 6 | Type of light source: | Lighting technology used: | LED | | |
| 7 | | Light source cap type (or other electric interface) | N/A | | |
| 8 | | Non-directional (NDLS) or directional (DLS): | NDLS | | |
| 9 | | Mains (MLS) or non-mains (NMLS): | MLS | | |
| 10 | | Connected light source (CLS): | no | | |
| 11 | | Colour-tunable light source: | no | | |
| 12 | | Envelope: | no | | |
| 13 | | High luminance light source: | no | | |
| 14 | | Anti-glare shield: | no | | |
| 15 | | Dimmable: | no | | |
| 16 | General product parameters: | Energy consumption in on-mode (kWh/1000 h) | 16 | kWh/1000h | |
| 17 | | Energy efficiency class | F | | |
| 18 | | Useful luminous flux (Φ_{use}), indicating if it refers to the flux in a sphere (360°), in a wide cone (120°) or in a narrow cone (90°), expressed in lm | 1700 | 360 | |
| 19 | | Correlated colour type | single value | | |
| 20 | | Correlated colour temperature, rounded to the nearest 100 K, or the range of correlated colour temperatures, rounded to the nearest 100 K, that can be set | 4000 | K | |
| 21 | | On-mode power (P_{on}), expressed in W and rounded to the first decimal | 16.0 | W | |
| 22 | | Standby power (P_{stb}), expressed in W and rounded to the second decimal | 0.00 | W | |
| 23 | | Networked standby power (P_{net}) for CLS, expressed in W and rounded to the second decimal | 0.00 | W | |
| 24 | | Colour rendering index, rounded to the nearest integer, or the range of CRI-values that can be set | 90 | | |
| 25 | | Outer dimensions without separate control gear, lighting control parts and nonlighting control parts, if any (millimetre) | | | |
| 26 | | Height (mm) | 294.00 | mm | |
| 27 | | Width (mm) | 294.00 | mm | |
| 28 | | Depth (mm) | 23.00 | mm | |
| 29 | | Spectral power distribution in the range 250 nm to 800 nm, at full-load (insert picture of the spectral power distribution + name of picture+extension (.jpg)) | CLEIP2TWC-D3018 WD_Spectral power distribution.jpg  | | |
| 30 | Claim of equivalent power | - | | | |
| 31 | If yes, equivalent power (W) | W | | | |
| 32 | Chromaticity coordinates (x and y) | 0.390;0.390 | | | |
| 33 | Parameters for directional light sources: | Peak luminous intensity (cd) | cd | | |
| 34 | | Beam angle in degrees (no decimal), or the range of beam angles that can be set | Degrees | | |
| 35 | Parameter for LED and OLED light sources: | R9 colour rendering index value | 0 | | |
| 36 | | Survival factor rounded to the second decimal (>0.xx) | 0.90 | | |
| 37 | | Lumen maintenance factor rounded to the second decimal (>0.xx) | 0.96 | | |
| 38 | Parameters for LED and OLED mains lights sources: | displacement factor ($\cos \phi$) rounded to the second decimal | 0.83 | | |
| 39 | | Colour consistency in McAdam ellipses | 4.5 | | |
| 40 | | Claims that an LED light source replaces a fluorescent light source without integrated ballast of a particular wattage. | - | | |
| 41 | | If yes then replacement claim (W) (no decimal) | W | | |
| 42 | | Flicker metric ($P_{st} L_{M0}$) rounded to the first decimal | 0.0 | | |
| 43 | | Stroboscopic effect metric (SVM) rounded to the first decimal | 0.1 | | |
| 44 | Technical documentation name (in case of light source product) | CLEIP2TWC-D3018 WD Technical documentation for light source.pdf | | | |
| 45 | Light source removing instruction name (in case of containing product) | | | | |