

AQUENCE FD 150/6

Known as Dorus FD 150/6 LS
December 2017

PRODUCT DESCRIPTION

AQUENCE FD 150/6 provides the following product characteristics:

Technology	PUR
Product Type	1C PUR Dispersion
Application	3D Application
Appearance	liquid transparent after drying

Application Areas

- Thermoforming presses (with and without membrane)
- Furniture fronts for the living area

Product Properties

- Free of solvent
- Clean spraying
- High green tack
- Highest heat and moisture resistance
- Sealable at lowest temperature

Technical Data

AQUENCE FD 150/6:

pH value (20 °C) ISO 976	7 to 10
Viscosity, Brookfield - RVT, 3/20/20, mPa.s ISO 2555	2,000 to 3,500

DIRECTIONS OF USE

Preliminary Statement

Prior to application it is necessary to read the **Material Safety Data Sheet** for information about precautionary measures and safety recommendations. Also, for chemical products exempt from compulsory labeling, the relevant precautions should always be observed. Please also refer to the local safety instructions and contact Henkel for analytical support.

Instructions for Use

In general, AQUENCE FD 150/6 is a one-component glue system - without additional cross-linker.

The working temperature of the workpiece and glue should be over +18°C to achieve optimal bonding results. Lower working temperature results in higher viscosity of the glue. The glue mix is sprayed with an appropriate spraying gun (nozzle size: 1,4 to 2 mm). As a rule, it is sufficient to apply one coat to the flat surface. Open pore inner and outer radii, however, need to be coated a second time after a brief drying interval. The pre-glued pieces should be sealed within 2 days to achieve optimum bond.

Please note

Temperatures above +25°C will shorten the max. storage time of pre-coated fronts significantly.

Drying time, minutes depending on temperature, humidity and quantity applied	≥30
Activation temperature in the glue line, °C at the edges	≥55
Curing time, hours complete curing after 7 days	24

All parts which come into contact with the glue must be made either of stainless steel (V2A/V4A) or plastic.

Cleaning

Equipment used to apply the glue may be cleaned easily using cold or luke-warm water before the adhesive has dried hard. Hard dried glue remnants have to be removed mechanically.

STORAGE

The glue should be transported and stored in the tightly closed original container at temperatures above + 10 °C and below max. + 30 °C.

Cooling below +10 °C can lead to coagulation.
Storage life up to 6 months.

Classification:

Please refer to the corresponding **safety data sheets** for details on:

Hazardous Information
Transport Regulations
Safety Regulations

ADDITIONAL INFORMATION**Disclaimer****Note:**

The information provided in this Technical Data Sheet (TDS) including the recommendations for use and application of the product are based on our knowledge and experience of the product as at the date of this TDS. The product can have a variety of different applications as well as differing application and working conditions in your environment that are beyond our control. Henkel is, therefore, not liable for the suitability of our product for the production processes and conditions in respect of which you use them, as well as the intended applications and results. We strongly recommend that you carry out your own prior trials to confirm such suitability of our product.

Any liability in respect of the information in the Technical Data Sheet or any other written or oral recommendation(s) regarding the concerned product is excluded, except if otherwise explicitly agreed and except in relation to death or personal injury caused by our negligence and any liability under any applicable mandatory product liability law.

In case products are delivered by Henkel Belgium NV, Henkel Electronic Materials NV, Henkel Nederland BV, Henkel Technologies France SAS and Henkel France SA please additionally note the following:

In case Henkel would be nevertheless held liable, on whatever legal ground, Henkel's liability will in no event exceed the amount of the concerned delivery.

In case products are delivered by Henkel Colombiana, S.A.S. the following disclaimer is applicable:

The information provided in this Technical Data Sheet (TDS) including the recommendations for use and application of the product are based on our knowledge and experience of the product as at the date of this TDS. Henkel is, therefore, not liable for the suitability of our product for the production processes and conditions in respect of which you use them, as well as the intended applications and results. We strongly recommend that you carry out your own prior trials to confirm such suitability of our product.

Any liability in respect of the information in the Technical Data Sheet or any other written or oral recommendation(s) regarding the concerned product is excluded, except if otherwise explicitly agreed and except in relation to death or personal injury caused by our negligence and any liability under any applicable mandatory product liability law.

In case products are delivered by Henkel Corporation, Resin Technology Group, Inc., or Henkel Canada Corporation, the following disclaimer is applicable:

The data contained herein are furnished for information only and are believed to be reliable. We cannot assume responsibility for the results obtained by others over whose methods we have no control. It is the user's responsibility to determine suitability for the user's purpose of any production methods mentioned herein and to adopt such precautions as may be advisable for the protection of property and of persons against any hazards that may be involved in the handling and use thereof. In light of the foregoing, **Henkel Corporation specifically disclaims all warranties expressed or implied, including warranties of merchantability or fitness for a particular purpose, arising from sale or use of Henkel Corporation's products. Henkel Corporation specifically disclaims any liability for consequential or incidental damages of any kind, including lost profits.** The discussion herein of various processes or compositions is not to be interpreted as representation that they are free from domination of patents owned by others or as a license under any Henkel Corporation patents that may cover such processes or compositions. We recommend that each prospective user test his proposed application before repetitive use, using this data as a guide. This product may be covered by one or more United States or foreign patents or patent applications.

Trademark usage: [Except as otherwise noted] All trademarks in this document are trademarks and/or registered trademarks of Henkel and its affiliates in the U.S. and elsewhere.

Reference 0.2

Henkel AG & Co. KGaA
73438 Bopfinger, Germany
Phone: +49-7362-81-0

Henkel Corporation
Bridgewater, NJ 08807, USA
Phone: +1-908-685-7000

Henkel (China) Co.Ltd.
201203 Shanghai, China
Phone: +86-21-2891-8000

For more information contact us on www.henkel.com