


1	General information	Supplier's name or trade mark			
2		Supplier's address	ADEO Services, 135 rue Sadi Carnot - CS00001, 59790 RONCHIN		
3		Model Identifier - Luminaire Supplier reference	780254 / 780269		
4		Light sources maker model	MLS		
5		Date of placement on the market	01/06/2022		
6	Type of light source:	Lighting technology used:	LED		
7		Light source cap type (or other electric interface)	/		
8		Non-directional (NDLS) or directional (DLS):	NDLS		
9		Mains (MLS) or non-mains (NMLS):	NMLS		
10		Connected light source (CLS):	no		
11		Colour-tuneable light source:	no		
12		Envelope:	no		
13		High luminance light source:	no		
14		Anti-glare shield:	no		
15		Dimmable:	no		
16	General product parameters:	Energy consumption in on-mode (kWh/1000 h)	9	KWh/1000h	
17		Energy efficiency class	E		
18		Useful luminous flux (Φ_{use}) , indicating if it refers to the flux in a sphere (360°), in a wide cone (120°) or in a narrow cone (90°), expressed in Lm	1050 (360°)		
19		Correlated colour type	single value		
20		Correlated colour temperature, rounded to the nearest 100 K, or the range of correlated colour temperatures, rounded to the nearest 100 K, that can be set	4000	K	
21		On-mode power (P_{on}), expressed in W and rounded to the first decimal	8,5	W	
22		Standby power (P_{sb}), expressed in W and rounded to the second decimal	0,00	W	
23		Networked standby power (P_{net}) for CLS, expressed in W and rounded to the second decimal	0,00	W	
24		Colour rendering index, rounded to the nearest integer, or the range of CRI-values that can be set	81		
25		Outer dimensions without separate control gear, lighting control parts and nonlighting control parts, if any (millimetre)			
26		Height (mm)	600,00	mm	
27		Width (mm)	13,00	mm	
28		Depth (mm)	1,00	mm	
29		Spectral power distribution in the range 250 nm to 800 nm, at full-load (insert picture of the spectral power distribution + name of picture+extension (.jpeg))			
30	Claim of equivalent power	-			
31	If yes, equivalent power (W)				
32	Chromaticity coordinates (x and y)	0,376 / 0,373			
33	Parameters directional light sources:	Peak luminous intensity (cd)			
34		Beam angle in degrees (no decimal), or the range of beam angles that can be set	360	Degrees	
35	meter for LED OLED light sources:	R9 colour rendering index value	7		
36		Survival factor rounded to the second decimal (>0.xx)			

37	Parameters for LED and OLED mains lights sources:	Lumen maintenance factor rounded to the second decimal (>0.xx)		
38		displacement factor (cos ϕ_1) rounded to the second decimal	0,90	
39		Colour consistency in McAdam ellipses		
40		Claims that an LED light source replaces a fluorescent light source without integrated ballast of a particular wattage.	-	
41		If yes then replacement claim (W) (no decimal)		W
42		Flicker metric (Pst LM) rounded to the first decimal	0,0	
43		Stroboscopic effect metric (SVM) rounded to the first decimal	0,0	
44	Technical documentation name (in case of light source product)			
45	Light source removing instruction name (in case of containing product)			

