

TECHNICAL PRODUCT SHEET

MODEL	BASTILLE MAT 60X120 WHITE	
SIZE	NOMINAL SIZE: 60x120 / 23,62"x47,60"	
	WORK SIZE (W) in mm: 600'0 x 1200'0 x 10,3	
REQUIREMENTS	X	PORCELAIN WHITE BODY RED BODY
DIMENSIONS AND SURFACE QUALITY	X	RECTIFIED MATT
		RECTIFIED POLISHED OR SEMIPOLISHED
		RECTIFIED SOFT POLISHED
		RECTIFIED BRIGHT
		BRIGHT (NO RECTIFIED)
		MATT(NO RECTIFIED)

PROPIEDADES	NORMA UNE-EN 14411		AZTECA CERÁMICA		TEST
		%	mm	%	
DIMENSIONS AND SURFACE QUALITY					
LENGTH (L) AND WIDTH (W) The deviation of the average size for each tile (2 or 4 sides) from the work size (W)	± 2.0	± 0.60 %	± 0.5	± 0.08 % / ± 0.04 %	ISO 10545-2
THICKNESS The deviation of the average thickness of each tile from the work size thickness.	± 0.5	± 5%	± 0.2	± 2.0 %	ISO 10545-2
STRAIGHTNESS OF SIDES (FACIAL SIDES) The maximum deviation from straightness, in mm, related to the corresponding work sizes.	±1.5	± 0.50 %	± 1.0	± 0.20 % / ± 0.10 %	ISO 10545-2
RECTANGULARITY The maximum deviation from rectangularity, in mm, related to the corresponding work sizes.	±2.0	± 0.50 %	± 1.0	± 0.20 % / ± 0.10 %	ISO 10545-2
SURFACE FLATNESS The maximum deviation from flatness in mm: A) Centre curvature, related to diagonal calculated from the work sizes. B) Edge curvature, related to the corresponding work sizes. C) Warpage, related to diagonal calculated from the work sizes	±2.0	± 0.50 %	+1.2 / -1.0	+ 0.09 % / - 0.07 % + 0.10 % / - 0.08% + 0.20 % / - 0.17 %	ISO 10545-2

RECOMMENDED USE	
Glazed wall tiles. Not recommended for floors.	A
For light transit areas with soft soled footwear, such as private bathrooms and bedrooms without direct access to the outside. Any abrasion should be avoided	B
For medium transit areas with soft soled or normal footwear, for example, rooms in the living areas of a home with the exception of entrances, and other rooms that may have a lot of traffic.	C
For medium transit areas with normal footwear. Recommended for all areas of private home (kitchens, entrances, corridors and terraces), as well as offices, consulting rooms and other places of similar use. Medium resistance to abrasion.	D
For areas of regular transit, such as commercial zones, hotels, exhibition rooms and shops. Fairly high resistance to abrasion.	E X
HIGH TRANSIT, floor tiles especially designed for areas of heavy transit. Highly resistant to wear.	HIGH TRANSIT

