




J&J India Sourcing LLP

Product Specification Sheet- Hard Flooring

General Information						
Customer		ADEO SERVICES		Vendor	LAVISH GRANITO PVT LTD	
Item Description			FLOOR/WALL TILE ARTENS INTENSO PULPIS SILVER POLISHED RECT 60X60		Size cm	60X60CM
Client ref #	Vendor ref #	Unit EAN Code	Color	Packaging Description		
82694581	LAV600x600-P-PULPIS SILVER	3276007369229	Silver	Unit	1 BOX-3 tiles	
				Inner	NA	
				Master	NA	
				Pallet	46 -BOXES -138 TILES	
BRAND/NONAME	BRAND NAME					
<input checked="" type="checkbox"/> -BRAND	ARTENS					
<input type="checkbox"/> -NONAME						
Labels and Other Packaging Accessories			Box of 3 tiles is one unit, unit boxes are strapped at 4 places. Unit boxes have Artens artworks printed on it, barcode, Adeo batch-code and vendors batch code are separately pasted on the unit box. 46-unit boxes are loaded on one pallet, corner protectors are used on pallets and then poly wrapped, and boxes are bundled with clear adhesive tapes. Finally, the whole pallet is strapped, and pallet marking is pasted on adjacent sides of pallet.			
1) Product Specification				Acceptance Criteria	Warning Labels/claims/Logo	
Material Composition				/	As mentioned in artwork	
Type Of tile		POLISHED GLAZED PORCELAIN TILE		/		
Type of finish		POLISHED		/		
Number of faces		10		/		
Net Weight / Pc(kg)		7.17		+/-3%		
Water absorption rate		<0.06 %		< 0.50%		
Straightness of sides		-0.05		+/-0.5%		
Rectangularity		-0.06		+/-0.5%		
Rectified or unrectified		RECTIFIED		/		
Glossiness value		ABOVE 100		/		
Breaking strength (N)		1630 N		>1300N		
MOR(N/mm2)		43.1 N/MM2		>30		
Quality of surface		ABOVE 95 %		>95%		
Surface flatness		+/- 0.04 %		+/-0.5%		
Hardness		5		5		
2) Digital/CAD of the Product				Measurements		
				DESCRIPTION	VALUE	TOLERANCE
					CM	std
				length	60	+/-0.5%
				width	60	+/-0.5%
				Thickness	8.75	+/-5%
Diagonal length	84.85	+/-0.5%				
				3) Quality Points:		
				1) Surface defects* should not be visible on tile surface when viewed from 1m dist		
				2) Slight shade variation form one production batch to another is acceptable but it needs to be controlled and inspected during PSI		
				3) "Made in India" stamp at back side is mandatory.		
4) Test requirements (Please refer Adeo Test Protocol for test method, Acceptance criteria and Report Validity)						
Onsite Physical tests:						